

# Symbol LS9208i

## Hands-free omni-directional presentation scanner



### FEATURES

#### High-performance, 100-line rastering omni-directional scan pattern

Increased productivity for novice and expert users, resulting in shorter checkout lines, better customer service

#### Single line scan pattern

Perfect for reading bar code menus and pick lists

#### Remote scanner management (RSM)

Reduces total cost of ownership by enabling remote, network-based device management

#### High-performance optics

Delivers superior data capture, even on high density bar codes

#### Extra loud beeper (85dBA)

Confirms positive decode feedback in noisy environments

#### Multiple onboard interfaces

Flexible host connectivity protects your hardware investment

#### Universal cables

Allows for easy replacement and/or upgrades

### Speed and versatility combine for increased productivity at checkout

The Symbol LS9208i presentation scanner from Motorola delivers both a high-performance processor and an innovative 100-line rastering omni-directional scan pattern for increased productivity at checkout, resulting in higher customer satisfaction. Built for both speed and versatility, the Symbol LS9208i features a small footprint, choice of colors and an optional, adjustable multi-mount stand that is easily adaptable to many point-of-sale environments. And, the extra loud beeper (85dBA) helps users ensure that the bar code has been read.

### Flexibility to meet the needs of many applications

Capable of reading a wide range of bar codes – from 13 mil (100% UPC) to 4 mil (Code 39) – the Symbol LS9208i enables streamlining of a variety of everyday processes in retail and other environments. In retail operations, such as convenience, grocery, department and specialty stores, the scanner improves throughput at the checkout counter, instantly deactivates EAS security tags and can even help workers identify a product in the back room. In a drug store or pharmacy, the device can also be used to help meet regulatory requirements by verifying prescriptions and managing the administration associated with certain over-the-counter but controlled substances. Employees can quickly scan badges to track time and attendance. Since there is no need to orient the scanner and the bar code, even patrons in a library can scan books in and out — keeping checkout lines moving and check-in bins empty. And, the extra loud 85dBA beeper helps ensure positive user feedback in noisy environments.

### Robust new features offer easy set up and reduced costs

With the 123Scan setup utility, programming and configuring the Symbol LS9208i is made easy and minimizes startup time wherever the scanner is used. The remote scanner management capability enables centralized, network-based scanner deployment and management, dramatically reducing costs. What's more, multiple onboard interfaces and universal cables further reduce your inventory requirements. For the most investment protection, the Symbol LS9208i also features built-in shock absorption that adds unmatched durability for a scanner in this class. The Symbol LS9208i offers premium features and powerful performance to help you save time and money.

### Today's most advanced presentation scanner from a global leader

In many applications, the feature-rich Symbol LS9208i presentation scanner offers aggressive performance, maximum durability and optimal ergonomics to create a more productive POS environment. When you buy the Symbol LS9208i, you receive the added assurance of purchasing from Motorola — a company with proven solutions and millions of scanner installations worldwide.

To learn how the Symbol LS9208i presentation scanner can work for you, visit [www.motorola.com/ls9208i](http://www.motorola.com/ls9208i), or access our global contact directory at [www.motorola.com/enterprisemobility/contactus](http://www.motorola.com/enterprisemobility/contactus).

**Small footprint**  
Fits into the tightest cash/wrap environment

**Adjustable multimount stand**  
Optimize operator comfort and efficiency

**Built-in shock absorption**  
Protects scan module assembly increasing durability

**Flash memory**  
Facilitates updates and customization of product in the field

**Checkpoint Electronic Article Surveillance (EAS) deactivation option**  
Integrated antenna saves valuable counter space

**Supports 123Scan setup utility**  
Flexible setup using PC download

**Reads GS1DataBar (formerly RSS) Symbologies**  
Compatibility with new symbology leverages your hardware investment

**Global Trade Item Number (GTIN) Compliant**  
Capable of decoding and transmitting 14-digit GTINs, where appropriate

**Advanced Data Formatting (ADF)**  
Enables users to modify data prior to sending to host computer, eliminating costly modifications to the host software

## Symbol LS9208i Specifications

### Physical Characteristics

Dimensions: (without stand)	5.51 in. H x 3.49 in. W x 2.96 in. D 14 cm H x 8.8 cm W x 7.5 cm D
Dimensions: (w/ adjustable stand)	7.18 in. H x 4.83 in. W x 3.73 in. D 18.24 cm H x 12.27 cm W x 9.47 cm D
Weight:	Scanner only: 10.2 oz./320 g With adjustable stand: 21.5 oz./670 g
Power Source:	Depending on host: • Host power • External power supply
Voltage:	5.0 VDC $\pm$ 10%
Nominal Current:	390 mA
Power:	2 watts
Mounting Options:	Adjustable multi-mount stand
Color:	Cash Register White or Twilight Black

### Performance Characteristics

Light Source:	650 nm visible laser diode
Roll (Tilt) <sup>1</sup> :	Omni-directional: 360° Single-scan line: $\pm$ 40°
Pitch <sup>2</sup> :	Omni-directional: $\pm$ 50° Single-scan line: $\pm$ 60°
Skew (Yaw) <sup>3</sup> :	Omni-directional: $\pm$ 50° Single-scan line: $\pm$ 50°
Print Contrast:	25% minimum reflective difference
Scan Patterns:	Omni-directional: 20 interlocking lines, 4 scan angles, 4 lines per angle rastering @ 5 Hz Single scan line capability
Scan Rate:	Omni-directional: 1500 scans/second Single scan line: 75 scans/second
Depth of Field:	0 to 9 in./0 to 22.9 cm @ 13 mil (100% UPC/EAN)
Nominal Working Range:	See chart below
Width of Field:	1.6 in./40 mm @ face 6.7 in./170 mm @ 9 in.
Minimum Resolution:	4 mil
Decode Capability:	UPC/EAN/JAN, UPC/EAN w/ Supplementals, UCC/EAN128, Code 128, ISBT 128, Code 39, Trioptic Code 39, Interleaved 2 of 5, Discrete 2 of 5, Code 93, Code 11, Codabar, MSI, GS1 DataBar (formerly RSS)
Interfaces Supported:	USB, RS232, IBM® 468X/9X, Keyboard Wedge, Wand and Synapse™ (allows connectivity to virtually every POS host type)

### User Environment

Operating Temp.:	32° to 104° F/0° to 40° C
Storage Temp.:	-40° to 158° F/-40° to 70° C
Humidity:	5% to 95% non-condensing
Ambient Light Immunity:	Immune to normal artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, incandescent, mercury vapor and sodium vapor: 450 ft-candles (4,844 lux) Sunlight: 8,000 ft-candles (86,111 lux)
EAS Support:	Optional Checkpoint Electronic Article Surveillance EAS

### Regulatory

Electrical Safety:	Certified to UL 1950, CSA C22.2 No. 950 EN60825
Laser Safety:	CDRH Class IIa Laser Product IEC 60825 Class 1 Laser Product
EMC	CISPR B, FCC B

### Warranty

The Symbol LS9208i omni-directional scanner is warranted against defects in workmanship and materials for a period of 30 months from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See the complete warranty for details.

- Roll (Tilt): Controlled by rotating the wrist clockwise or counter-clockwise
- Pitch Controlled by dropping or raising the wrist
- Skew (Yaw): Controlled by rotating the wrist from left to right or vice versa

The above performance characteristics refer to 100% UPC bar code at 80% contrast located at 4 in./10 cm from nose of the scanner.

### LS9208i Decode Zone

Label Density	Depth of Field	
	LS9208i	
Paper Label	English	Metric
4 mil - Code 39	1.0" - 2"	2.5 - 5.1cm
5 mil - Code 39	1.0" - 3"	2.5 - 7.6cm
7.8 mil - 60% UPC	0.0" - 6"	0.0 - 15.2cm
10.4 mil - 80% UPC	0.0" - 7"	0.0 - 17.8cm
13 mil - 100% UPC	0.0" - 8.5"	0.0 - 21.6cm